

ZX1



IncredibleSound

It's your music, your voice, your message.

You need a speaker that can reproduce every note, every inspirational word

and every nuance of your style. Introducing ZX1. Compact, lightweight, yet high performance, ZX1 is a reflection of the needs of the high-speed,

time-crunched, high-tech lifestyle you lead. Its versatility is matched only by your imagination, and its look is pure beauty. So while your audience may not be fully aware

of why you sound incredible, you'll know it's because you

chose the very best. . .

ZX1





ZXI offers a wide array of mounting options including an integrated pole mount and removable rubber feet that hide M8 mounting studs. Dual NL4 connectors and an ergonomic molded carrying slot make **ZXI** perfect for portable music, AV rental and mobile audio applications.

ZXI shines in monitor wedge applications, especially where the reproduction of vocal frequencies is crucial. Its asymmetrical cabinet design means you simply have to put **ZXI** on its side to achieve a 45° monitor angle. And with the ability to rotate its 90° x 50° horn, you can adjust the dispersion pattern to suit your unique application.

	ZX1-90 Portable Version	ZX1i-90 Fixed Install Version	ZX1i-100 Fixed Install Version	ZX1i-100t 70v/100v Version
Frequency Response⁽¹⁾ (-3 dB)	60 Hz - 20 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz	60 Hz - 20 kHz
Frequency Range⁽¹⁾ (-10 dB)	48 Hz - 20 kHz	48 Hz - 20 kHz	48 Hz - 20 kHz	48 Hz - 20 kHz
Axial Sensitivity⁽¹⁾	94 dB (1W/1m)	94 dB (1W/1m)	92 dB (1W/1m)	92 dB (1W/1m)
Maximum Calculated SPL	125 dB	125 dB	121 dB	121 dB
Horizontal Coverage	90° or 50°	90° or 50°	100°	100°
Vertical Coverage	50° or 90°	50° or 90°	100°	100°
System Power Handling	200W Continuous, 400W Program	200W Continuous, 400W Program	200W Continuous, 400W Program	200W Continuous, 400W Program
LF Transducer	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver	EV8L, 8 in (203mm) Driver
HF Transducer	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver	DH2005, 1 in. (25.4mm) Exit Compression Driver
Nominal Impedance	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Pole Mount	Included	N/A	N/A	N/A
Transformer Taps	N/A	N/A	N/A	6.5, 12.5, 25, 50, 100 watts 70/100v
Connectors	Two NL4 Connectors	4-Pin detachable Phoenix style	4-Pin detachable Phoenix style	4-Pin detachable Phoenix style
Overload Protection	Full protection – all modes	Full protection – all modes	Full protection – all modes	Full protection – all modes
Mounting System	Four M8 studs on bottom of speaker	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket	QuickSAM™ Heavy-Duty Strong-Arm Mounting Bracket
Built-In Monitor Angle	Yes	No	No	No
Available Colors	Black	Black/White	Black/White	Black/White
Included Accessories	None	QuickSAM™ Mount	QuickSAM™ Mount	QuickSAM™ Mount
Dimensions (H x W x D)	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm	17.75" x 11.12" x 10.35" 451mm x 282mm x 263mm
Net Weight	8.4 kg (18.5 lbs)	8.4 kg (18.5 lbs)	8.4 kg (18.5 lbs)	10.4 kg (23.0 lbs)
Shipping Weight	10.2 kg (22.5 lbs)	10.2 kg (22.5 lbs)	10.2 kg (22.5 lbs)	12.3 kg (27.0 lbs)

(1) Half-space measurements

© EVI Audio GmbH 09/05 • Printed in Germany (BECK) • SUBJECT TO CHANGE WITHOUT PRIOR NOTICE • Order # 160 060

The Complete ZXI Family

The ZXI is part of a complete compact speaker system product line with models for fixed installation distributed systems.



Americas

Telex Communications Inc.
12000 Portland Ave South,
Burnsville, MN 55337, USA
USA—Phone: 1-800-392-3497, Fax: 1-800-955-6831
Canada—Phone: 1-866-505-5551, Fax: 1-866-336-9467
Latin America—Phone: 1-952-887-5532, Fax: 1-952-736-4212

Europe, Africa & Middle-East

EVI Audio GmbH
Hirschberger Ring 45,
D 94315 Straubing, Germany
Phone: +49 9421 706-0, Fax: +49 9421 706-265

UK: Shuttlesound
4 The Willows Centre,
Willow Lane,
Mitcham, Surrey CR4 4NK, UK
Phone: +44 208 646 7114
Fax: +44 208 640 7583

Asia & Pacific Rim

Japan: EVI Audio Japan Ltd.
5-3-8 Funabashi, Setagaya-Ku,
Tokyo, Japan 156-0055
Phone: +81 3-5316-5020,
Fax: +81 3-5316-5031

Australia: APAC Audio Pty Ltd.
James Ruse Business Park
Unit 2C 6 Boundary Road
Northmead NSW 2152
Phone: +61 2 9683 4752
Fax: +61 2 9890 5928

China: EVI Audio Ltd.
Room 2210-2215, Tower B, Far East International
Plaza, No. 317, Xianxia Road,
Shanghai, China, Post Code: 200051
Phone: +86 (21) 6235-1677
Fax: +86 (21) 6235-1676

Hong Kong: EVI Audio Ltd.
Unit 5, 1/F, Topsail Plaza
11 On Shum Street
Shek Mun, Shatin
Hong Kong
Phone: +852 2351-3628, Fax: +852 2351-3329

Singapore: Telex Pte. Ltd.
3015A Ubi Road 1, 05-10
Kompong Ubi Industrial Estate, Singapore 408705
Phone: +65 6746-8760, Fax: +65 6746-1206

Live For Sound™
www.electrovoice.com

